

Trans Technical Solutions

Tel: +27 11 974 9679
Fax: +27 11 974 9653
Email: sales@ttsafrica.com

P O Box 5094
Delmenville
1403

Unit F11, Roete 24
Meadowdale
Germiston



45 - 45° Connector Fixed External Male Thread



Type 45
45° Elbow Fitting

Type 45

45° Elbow Fitting - Fixed External Male Thread / For insertion into knockouts using a locknut. Locknut supplied with METRIC

THREAD ONLY

Materials: Polyamide (Nylon) 66

Colour: Black (BL), Grey (GR)

Part No.	Nominal Conduit Size	Metric Thread	Part No.	Nominal Conduit Size	PG Thread
TAL13/M16/45*	13mm	M16	TAL13/PG9/45*	13mm	PG9
TAL16/M16/45	16mm	M16	TAL16/PG11/45	16mm	PG11
TAL16/M20/45	16mm	M20	TAL16/PG13/45	16mm	PG13,5
TAL21/M20/45	21mm	M20	TAL21/PG13/45	21mm	PG13,5
			TAL21/PG16/45	21mm	PG16
TAL28/M25/45	28mm	M25	TAL28/PG21/45	28mm	PG21
TAL34/M32/45	34mm	M32	TAL34/PG29/45	34mm	PG29
TAL42/M50/45	42mm	M40	TAL42/PG36/45	42mm	PG36
TAL54/M50/45	54mm	M50	TAL54/PG48/45	54mm	PG48

To order quote part number & body colour, e.g. TAL 21/M20/45/BL

*These parts are not covered by the RU certification

Approvals



IP Rating

Appropriate Conduit

Temperature Range

For use with: Type PA / PI / CP / PR / PF

Static Applications: -50°C to +120°C

Moving Applications: -45°C to +120°C

IP Rating	Appropriate Conduit
IP66	Yes
IP67	Yes + ALS Seal
IP68	Yes + ALS Seal
IP69	Yes + ALS Seal