

S45 - 45° Elbow Connector Swivel External Male Thread



Type S45
45° Elbow Body

Type S45

45° Elbow Body - Swivel External Male Thread - For insertion into threaded entries & knockouts.

Order locknuts separately

Materials: Polyamide (Nylon) 66, Nickel Plated Brass Thread/TPE

Colour: Black (BL), Grey (GR) / Yellow (Y), Blue (B) Elastomer

Part No.	Nominal Conduit Size	Metric Thread	Part No.	Nominal Conduit Size	NPT Thread
TAT13/M16/S45	13mm	M16	TAT13/038/S45	13mm	3/8"
TAT16/M16/S45	16mm	M16	TAT16/038/S45	16mm	3/8"
TAT21/M20/S45	21mm	M20	TAT21/050/S45	21mm	1/2"
TAT28/M25/S45	28mm	M25	TAT28/075/S45	28mm	3/4"
TAT34/M32/S45	34mm	M32	TAT34/100/S45	34mm	1"
TAT42/M40/S45	42mm	M40	TAT42/125/S45	42mm	1 1/4"
TAT48/M50/S45	48mm	M50	TAT48/150/S45	48mm	1 1/2"
TAT54/M50/S45	54mm	M50	TAT54/150/S45	54mm	1 1/2"
TAT54/M63/S45	54mm	M63	TAT54/200/S45	54mm	2"

To order quote part number, body colour & Elastomer colour, e.g. TAT54/M63/S45/BLB

Approvals



Blue Elastomer Version Only



IP Rating

For use with: Type PA / PI / PR / PADL / PF

IP Rating	Appropriate Conduit
IP40	Yes
IP65	Yes
IP68	Yes (4 bar 30mins)
IP69	Yes

Temperature Range

Static Applications: -50°C to +120°C

Moving Applications: -45°C to +120°C

Fitting Characteristics

