

Trans Technical Solutions

Tel: +27 11 974 9679
 Fax: +27 11 974 9653
 Email: sales@ttsafrica.com

P O Box 5094
 Delmerville
 1403

Unit F11, Roete 24
 Meadowdale
 Germiston



Technical Data | KPEX-0027.1

Female to female thread coupler



Features

- Straight through female to female coupler

Approvals



Certification & Standards

Approved to:	IEC EN 60079-0, 60079-1, 60079-7, 60079-31
EC TYPE Examination Certificate:	ATEX: BASEFFA08ATEX0359U IECEX: IECEX BAS 08.0121U Ex e IIC Gb Ex tb IIIC Db
Safe operating temperature range:	-60°C to +200°C

Part No.	Metric Thread Size (mm)	Part No.	Metric Thread Size (mm)	Part No.	Metric Thread Size (mm)
Nickel Plated		Brass		Stainless Steel	
TEXN/M16/C	16	TEX/M16/C	16	TEXS/M16/C	16
TEXN/M20/C	20	TEX/M20/C	20	TEXS/M20/C	20
TEXN/M25/C	25	TEX/M25/C	25	TEXS/M25/C	25
TEXN/M32/C	32	TEX/M32/C	32	TEXS/M32/C	32
TEXN/M40/C	40	TEX/M40/C	40	TEXS/M40/C	40
TEXN/M50/C	50	TEX/M50/C	50	TEXS/M50/C	50
TEXN/M63/C	63	TEX/M63/C	63	TEXS/M63/C	63
TEXN/M75/C	75	TEX/M75/C	75	TEXS/M75/C	75

Part No.	NPT Thread Size (inch)	Part No.	NPT Thread Size (inch)	Part No.	NPT Thread Size (inch)
Nickel Plated		Brass		Stainless Steel	
TEXN/038/C	3/8	TEX/038/C	3/8	TEXS/038/C	3/8
TEXN/050/C	1/2	TEX/050/C	1/2	TEXS/050/C	1/2
TEXN/075/C	3/4	TEX/075/C	3/4	TEXS/075/C	3/4
TEXN/100/C	1	TEX/100/C	1	TEXS/100/C	1
TEXN/125/C	1 1/4	TEX/125/C	1 1/4	TEXS/125/C	1 1/4
TEXN/150/C	1 1/2	TEX/150/C	1 1/2	TEXS/150/C	1 1/2
TEXN/200/C	2	TEX/200/C	2	TEXS/200/C	2
TEXN/250/C	2 1/2	TEX/250/C	2 1/2	TEXS/250/C	2 1/2