



# Metallic Accessories



## Couplers

**Coupler** - Female to Female thread couplers for use in both Exd and Exe applications



### Certification & Standards

**Certification Standard:**  
 Baseefa 08 ATEX 0359U  
 IECEx BAS08.0121U

**Temperature:** -60°C to +200°C

### Technical Specifications

Type	Metric Thread Size (mm)	16	20	25	32	40	50	63	75
	PG Thread Size	3/4	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Metric - Brass		T/EX/M16/C	T/EX/M20/C	T/EX/M25/C	T/EX/M32/C	T/EX/M40/C	T/EX/M50/C	T/EX/M63/C	T/EX/M75/C
NPT Thread - Brass		T/EX/038/C	T/EX/050/C	T/EX/075/C	T/EX/100/C	T/EX/125/C	T/EX/150/C	T/EX/200/C	T/EX/250/P

*\*For Nickel Plated Brass add EXN and for Stainless Steel add EXS, e.g. EXS/M16/C*

## Hex Locknuts

**Hex Locknut** - for Metric Threads and NPT Threads (Nickel Plated Brass only)



### Technical Specifications

Type	Metric Thread Size (mm)	16	20	25	32	40	50	63	75
	PG Thread Size	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Metric - Stainless Steel		-	T/MXWH04	T/MXWH05	T/MXWH06	T/MXWH07	T/MXWH08	-	-
Metric - Brass		T/WHMB03	T/WHMB04	T/WHMB05	T/WHMB06	T/WHMB07	T/WHMB08	-	-
Metric - Nickel Plated Brass		T/WHMM03	T/WHMM04	T/WHMM05	T/WHMM06	T/WHMM07W	<b>T/WHMM08</b>	T/WHMM09	-
NPT Thread - Nickel Plated Brass		-	<b>T/WHAM04</b>	<b>T/WHAM05</b>	<b>T/WHAM06</b>	<b>T/WHAM07</b>	<b>T/WHAM08W</b>	-	-



# Metallic Accessories

## Sealing Joint Washers

**Sealing Joint Washer** - for use with all ATEX and IECEx approved products (Nylon only)



### Certification & Standards

**Certification Standard:** Nylon Metric approved for use with all ATEX / IECEx products

### Technical Specifications

	16	20	25	32	40	50	63	75
Metric Thread Size (mm)	16	20	25	32	40	50	63	75
PG Thread Size	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Outside Diameter (mm)	22	26	34.3	41.5	52	66.5	84.5	-
Type Thickness (mm)	1.6	1.6	1.7	1.7	2	2	2	-
Metric - Nylon (ATEX / IECEx approved)	T/EXFM03	TET/XFM03	T/EXFM03	T/EXFM03	T/EXFM03	T/EXFM03	T/EXFM03	-
Metric - Fibre	T/WHMB03	T/WHMB04	T/WHMB05	T/WHMB06	T/WHMB07	T/WHMB08	-	-

## Earth Tags

**Earth Tag** - to be used to create an earthing bond on an enclosure, when a cable gland is used



### Technical Specifications

	16	20	25	32	40	50	63	75
Metric Thread Size (mm)	16	20	25	32	40	50	63	75
PG Thread Size	3/8	1/2	3/4	1	1 1/4	1 1/2	2	2 1/2
Earth Tag - Brass	T/EX/M16/TAG	T/EX/M20/TAG	T/EX/M25/TAG	T/EX/M32/TAG	T/EX/M40/TAG	T/EX/M53/TAG	T/EX/M63/TAG	T/EX/M75/TAG