

Trans Technical Solutions

Tel: +27 11 974 9679
Fax: +27 11 974 9653
Email: sales@ttsafrica.com

P O Box 5094
Delmenville
1403

Unit F11, Rooft 24
Meadowdale
Germiston



Non-metallic conduit systems Accessories Type MB Manifold Box



Type MB Manifold Box

Type MB

Manifold Box - Multiway Adapters / Non metallic enclosure which can be machined to take upto eight Adaptalok ATS™ fittings

Materials: Polyamide (Nylon) 66/TPE / **Colour:** Black (BL) Only / Yellow (Y) Elastomer

Part No.	External Dimensions Lid (mm) Dia X Height	External Dimensions Fixing Lugs (mm)	Max Threaded Entry Per Face
TMB21	100 x 40	120	M20
TMB34	136 x 55	155	M32

To order quote part number, body colour & Elastomer colour, e.g. MB21/BLY

Non metallic enclosure which can be machined to take upto eight Adaptalok ATS™ fittings (or other devices) in a variety of configurations and sizes, e.g. 'Y', 'T', 'X', 'V' etc.

Each box has a removable cover for ease of access. The box seal is moulded, so remains captive. Each manifold is provided with eight blank sides which require drilling/machining to suit the application. Manifolds can be supplied ready drilled to order, subject to minimum order quantities. Threaded fittings with locknuts can be used in each entry.

Approvals



IP Rating	Appropriate Fitting	Temperature Range	UV Resistance
For use with: All threaded fittings in this catalogue		Static Applications: -50°C to +120°C	Very High
IP66	Yes	Moving Applications: -45°C to +120°C	
IP67	Yes		
IP68	Yes (2 bar 30mins)		
IP69	Yes		