

ROTOCUT Conduit Cutting Tool

Introduction

Rotocut offers a simple but effective method for cutting 20mm and 25mm S, SS, SP, LFH-SP and SN steel conduit types.

Instructions

Adjust the clamping pin so that the conduit is just held in the recess. Squeeze the lever and body whilst rotating the cutting blade. When the blade appears on the inside of the conduit, release the pressure and remove the conduit.

A simple twist will then separate the two parts. Where the conduit is covered, the covering can be cut prior to separation. Spare blades are available.



General Information

Extended Product Type	ROTOCUT
Product ID	7TCA296050R0437
EAN	5020963002601
Catalog Description	ROTO COND CUTTER
Long Description	CONDUIT CUTTER

Ordering

EAN	5020963002601
Minimum Order Quantity	1 piece
Customs Tariff Number	8203400000

Dimensions

Product Net Weight	371.95 g
--------------------	----------

Container Information

Package Level 2 Units	1 piece
Package Level 2 Width	25.4 mm
Package Level 2 Height	25.4 mm
Package Level 2 Depth / Length	25.4 mm

Transtechanical Solutions
Unit F11 Roete 24, 50 Herman Street
Meadowdale, Germiston
Tel: 011 974 9679
Fax: 011 974 9653



ROTOCUT Conduit Cutting Tool

Additional Information

Product Main Type	FLEXIBLE CABLE PROTECTION
-------------------	---------------------------

Certificates and Declarations (Document Number)

Data Sheet, Technical Information	ROTOCUT
Instructions and Manuals	ROTOCUT

Classifications

WEEE Category	Product Not in WEEE Scope
---------------	---------------------------

Categories

Low Voltage Products and Systems → Installation Products → Cable Protection, Explosion Proof and Lighting → Flexible Cable Protection Systems