

ATS - Straight Connector Fixed External Male Thread



Type A
Straight Fitting

Approvals



Type A
Straight Fitting

Approvals



Type A

Straight Fitting - Fixed External Male Thread - For insertion into knockouts using a locknut. Locknuts supplied with METRIC thread

Materials: Polyamide (Nylon) 66/TPE

Colour: Black (BL), Grey (GR) / Yellow (Y) Elastomer

Part No.	Nominal Conduit Size	Metric Thread	Part No.	Nominal Conduit Size	PF Thread	Part No.	Nominal Conduit Size	NPT Thread
TAT13/M16/A	13mm	M16	TAT13/PF038/A	13mm	3/8"	TAT13/038/A	13mm	3/8"
TAT16/M16/A	16mm	M16	TAT16/PF038/A	16mm	3/8"	TAT16/038/A	16mm	3/8"
TAT16/M20/A	16mm	M20	TAT16/PF050/A	16mm	1/2"	TAT16/050/A	16mm	1/2"
TAT21/M20/A	21mm	M20	TAT21/PF050/A	21mm	1/2"	TAT21/050/A	21mm	1/2"
TAT21/M25/A	21mm	M25						
TAT28/M25/A	28mm	M25	TAT28/PF075/A	28mm	3/4"	TAT28/075/A	28mm	3/4"
TAT28/M32/A	28mm	M32						
TAT34/M32/A	34mm	M32	TAT34/PF100/A	34mm	1"	TAT34/100/A	34mm	1"
TAT34/M40/A	34mm	M40						
TAT42/M40/A	42mm	M40	TAT42/PF125/A	42mm	1 1/4"	TAT42/125/A	42mm	1 1/4"
TAT42/M50/A	42mm	M50						
TAT48/M50/A	48mm	M50	TAT48/PF150/A	48mm	1 1/2"	TAT48/150/A	48mm	1 1/2"
TAT54/M50/A	54mm	M50						
TAT54/M63/A	54mm	M63	TAT54/PF200/A	48mm	2"	TAT54/200/A	54mm	2"

To order quote part number, body colour & Elastomer colour, e.g. TAT21/M20/A/BLY

Type A

Straight Fitting - Fixed External Male Thread - For insertion into knockouts using a locknut. Locknuts supplied with METRIC thread

Materials: Polyamide (Nylon) 66/TPE

Colour: Black (BL), Grey (GR) / Blue (B) Elastomer

Part No.	Nominal Conduit Size	Metric Thread	Part No.	Nominal Conduit Size	NPT Thread
TAT13/M16/A	13mm	M16	TAT13/038/A	13mm	3/8"
TAT16/M16/A	16mm	M16	TAT16/038/A	16mm	3/8"
TAT16/M20/A	16mm	M20	TAT16/050/A	16mm	1/2"
TAT21/M20/A	21mm	M20	TAT21/050/A	21mm	1/2"
TAT21/M25/A	21mm	M25T			
TAT28/M25/A	28mm	M25	TAT28/075/A	28mm	3/4"
TAT28/M32/A	28mm	M32			
TAT34/M32/A	34mm	M32	TAT34/100/A	34mm	1"
TAT34/M40/A	34mm	M40			
TAT42/M40/A	42mm	M40	TAT42/125/A	42mm	1 1/4"
TAT42/M50/A	42mm	M50			
TAT48/M50/A	48mm	M50	TAT48/150/A	48mm	1 1/2"
TAT54/M50/A	54mm	M50			
TAT54/M63/A	54mm	M63	TAT54/200/A	54mm	2"

To order quote part number, body colour & Elastomer colour, e.g. TAT21/M20/A/BLB

IP Rating	Appropriate Conduit	Temperature Range
For use with: Type PA / PI / PR / PADL / PF		Static Applications: -50°C to +120°C
IP40	Yes	Moving Applications: -45°C to +120°C
IP65	Yes	
IP68	Yes (4 bar 30mins)	
IP69	Yes	