

Heat Shrink Busbar Tubing

Product Introduction:

Heat Shrink Busbar-BBT is a heat shrink tube, specially used to enhance the insulation properties of busbar in switchgears and substations.

Features:

- Tracking and arcing resistant
- UV resistant
- Flexible
- Flame retardant
- Application upto 36kV
- RoHS Compliant



Operating temperature	Minimum shrink temperature	Minimum full recovery temperature
-55°C to +105°C	90°C	110 °C

Standard Color: Brown Red.

Heat Shrink Busbar Tubing

Dimensions:

Part Number	Size (mm)	As supplied (mm)	After recovery (mm)						Applicable Busbars (mm)
			11kV		24kV		36kV		
		I.D. Min	I.D. Max	W.T. Min	I.D. Max	W.T. Min	I.D. Max	W.T. Min	
TBBT15	15	15	6	2.3	--	--	--	--	15
TBBT20	20	20	8	2.3	8	2.5	10	4.0	20/15
TBBT25	25	25	10	2.3	10	2.5	13	4.0	25
TBBT30	30	30	12	2.3	12	2.5	15	4.0	30/20
TBBT40	40	40	16	2.5	16	2.7	20	4.0	40/30
TBBT50	50	50	20	2.5	20	2.7	25	4.0	50/35
TBBT60	60	60	24	2.5	24	2.7	30	4.0	60/45
TBBT70	70	70	28	2.6	28	2.8	35	4.0	70/50
TBBT80	80	80	32	2.6	32	2.8	40	4.0	80/55
TBBT100	100	100	40	2.6	40	2.8	50	4.2	100/75
TBBT120	120	120	48	2.8	48	3.0	60	4.2	120/85
TBBT150	150	150	60	3.0	60	3.1	75	4.2	150/105
TBBT180	180	180	72	3.0	72	3.1	90	4.2	180/135

Note: Printing, special sizes or colors available on request.