



Connect and Protect

TransTechnical Solutions

Technical Data Sheet

Metallic Systems

Type 90° Brass Elbow

Technical Characteristics

Conforms to	BSI Kitemark KM-35161 Low voltage directive
-------------	--

Approvals and Standards



Degree of mechanical protection	Very High
---------------------------------	-----------

Degree of protection	IP 40 - Type TSs A & B fittings IP 54 - Type TSP A & B fittings IP66 - Type TSP M fittings IP67 - Type TSPL A, B & M fittings
----------------------	--

UV protection	Very High
---------------	-----------

Fitting Characteristics	90° combined fitting & elbow
-------------------------	------------------------------

Normal operating temperature range	Application	Min Temp	Max Temp
	Static	- 65°C	+150°C
	Dynamic	- 45°C	+150°C

For use with - Conduit Series	All Adaptaflex Metallic conduit fittings
-------------------------------	--

Fire performance	Test Standard	Performance Rating
	Not Rated	Not Rated

Chemical resistance & Storage data	See page 4
------------------------------------	------------

Type of material	Nickel Plated Brass
------------------	---------------------

Image



011 974 9671

sales@ttsafrica.com

Unit F11, Roete 24, 50 Herman Street, Meadowdale, Germiston, South Africa



Connect and Protect

TransTechnical Solutions

Technical Data Sheet

Non-Metallic Systems


Type 90° Brass Elbow

Dimensional and Thread Data - M Thread

Part No.	Thread A (mm)	Thread C (mm)	Dimensions (mm)				
			B	D	E	F	G
TB/M16/90	M16 X 1.5	M16 X 1.5	10	11	12	31	38
TB/M20/90	M20 X 1.5	M20 X 1.5	13	13	15.8	35	46
TB/M25/90	M25 X 1.5	M25 X 1.5	14	16	20.4	43.8	55.8
TB/M32/90	M32 X 1.5	M32 X 1.5	15	16	27	53.6	66.6
TB/M40/90	M40 X 1.5	M40 X 1.5	18	17	34.6	67	80.4
TB/M50/90	M50 X 1.5	M50 X 1.5	18	18	44.6	80.5	99

Thread Data

Metric	Standard thread conforming to EN60423 & BS3643		
Thread Size mm	Ext Thread Outside Diameter	Int Thread Inside Diameter	Pitch
M10	10	8.9	1
M12	12	10.4	1.5
M16	16	14.4	1.5
M20	20	18.4	1.5
M25	25	23.4	1.5
M32	32	30.4	1.5
M40	40	38.4	1.5
M50	50	48.4	1.5
M63	63	61.4	1.5
M75	75	73.4	1.5



011 974 9671

sales@ttsafrica.com

Unit F11, Roete 24, 50 Herman Street, Meadowdale, Germiston, South Africa