

Trans Technical Solutions

Tel: +27 11 974 9679
Fax: +27 11 974 9653
Email: sales@ttsafrica.com

P O Box 5094
Delmenville
1403

Unit F11, Roete 24
Meadowdale
Germiston



SA - Straight Metal Swivel External Male Thread



Type SA
Straight Fitting

Type SA

[Straight Fitting - Swivel External Male Thread](#) / For insertion into threaded entries & knockouts using a locknut.

Order locknut separately

Materials: Polyamide (Nylon) 66, Nickel Plated Brass Thread

Colour: Black (BL), Grey (GR)

Part No.	Nominal Conduit Size	Metric Thread	Part No.	Nominal Conduit Size	PG Thread
TAL13/M16/SA*	13mm	M16	TAL13/PG9/SA*	13mm	PG9
TAL16/M16/SA	16mm	M16	TAL16/PG11/SA	16mm	PG11
TAL21/M20/SA	21mm	M20	TAL21/PG13/SA	21mm	PG13,5
			TAL21/PG16/SA	21mm	PG16
TAL28/M25/SA	28mm	M25	TAL28/PG21/SA	28mm	PG21
TAL34/M32/SA	34mm	M32	TAL34/PG29/SA	34mm	PG29
TAL42/M40/SA	42mm	M40	TAL42/PG36/SA	42mm	PG36
TAL54/M50/SA	54mm	M50	TAL54/PG48/SA	54mm	PG48
TAL54/M63/SA	54mm	M63			

To order quote part number & body colour, e.g. TAL13/M16/SA/BL. NPT also available

*These parts are not covered by the RU certification

Approvals



IP Rating	Appropriate Conduit	Temperature Range
For use with: Type PA / PI / CP / PR / PF		Static Applications: -50°C to +120°C
IP66	Yes	Moving Applications: -45°C to +120°C
IP67	Yes + ALS Seal	Fitting Characteristics
IP68	Yes + ALS Seal	
IP69	Yes + ALS Seal	

