

Trans Technical Solutions

Tel: +27 11 974 9679
Fax: +27 11 974 9653
Email: sales@ttsafrica.com

P O Box 5094
Delmenville
1403

Unit F11, Roete 24
Meadowdale
Germiston



SF45 - 45° Elbow Connector Swivel Internal Female Thread



Type SF45
45° Elbow Body

Type SF45

45° Elbow Body - Swivel Internal Female Thread - For attaching to external threads & other fittings

Materials: Polyamide (Nylon) 66, Nickel Plated Brass Thread/TPE

Colour: Black (BL), Grey (GR) / Yellow (Y), Blue (B) Elastomer

Part No.	Nominal Conduit Size	Metric Thread	Part No.	Nominal Conduit Size	NPT Thread
TAT13/M16/SF45	13mm	M16	TAT13/038/SF45	13mm	3/8"
TAT16/M16/SF45	16mm	M16	TAT16/038/SF45	16mm	3/8"
TAT21/M20/SF45	21mm	M20	TAT21/050/SF45	21mm	1/2"
TAT28/M25/SF45	28mm	M25	TAT28/075/SF45	28mm	3/4"
TAT34/M32/SF45	34mm	M32	TAT34/100/SF45	34mm	1"
TAT42/M40/SF45	42mm	M40	TAT42/125/SF45	42mm	1 1/4"
TAT48/M50/SF45	48mm	M50	TAT48/150/SF45	48mm	1 1/2"
TAT54/M50/SF45	54mm	M50			
TAT54/M63/SF45	54mm	M63	TAT54/200/SF45	54mm	2"

To order quote part number, body colour & Elastomer colour, e.g. TAT16/M16/SF45/BLB

Approvals



Blue Elastomer Version Only



IP Rating

For use with: Type PA/PI/PR/PADL/PF

IP Rating	Appropriate Conduit
IP40	Yes
IP65	Yes
IP68	Yes (4 bar 30mins)
IP69	Yes

Appropriate Conduit

Temperature Range

Static Applications: -50°C to +120°C

Moving Applications: -45°C to +120°C

Fitting Characteristics

