



Connect and Protect

TransTechnical Solutions

Technical Data Sheet

Non-Metallic Systems

Sealing Washer

Technical Characteristics

Conforms to N/A

Approvals and Standards N/A

Degree of mechanical protection N/A

UV protection High

Fitting Characteristics Sealing washers used to maintain IP seal rating on various fittings

Normal operating temperature range	Application	Min Temp	Max Temp
	Static	- 40°C	+120°C
	Dynamic	- 5°C	+120°C

For use with - Conduit Series All Adaptaflex threaded fittings

Fire performance	Test Standard	Performance Rating
	Not Rated	Not Rated

Testing data N/A

Type of material Neoprene, Thermoplastic elastomer (TPE) & Nylon

Finish N/A

Image



011 974 9671

sales@ttsafrica.com

Unit F11, Roete 24, 50 Herman Street, Meadowdale, Germiston, South Africa



Connect and Protect

TransTechnical Solutions

Technical Data Sheet

Non-Metallic Systems

Sealing Washer

Dimensional Data

Part No	Colour	Material	Nominal Dimensions (mm)		
			A	B	C
SW/M12	Black	TPE	15.5	11.45	1
SW/M16	Black	TPE	21.5	15.8	1
SW/M20	Black	TPE	25.5	19.8	1
SW/M25	Black	TPE	34	24.8	1
SW/M32	Black	TPE	41.5	31.5	1
SW/M40	Black	TPE	53.3	39.5	1.5
SW/M50	Black	TPE	67	49.5	1.5
SW/M63	Black	TPE	70	62.6	2

TPE = Thermoplastic Elastomer

