

Trans Technical Solutions

Tel: +27 11 974 9679
Fax: +27 11 974 9653
Email: sales@ttsafrica.com

P O Box 5094
Delmenville
1403

Unit F11, Roefe 24
Meadowdale
Germiston



Nylon 6 Double Slit Conduit

Double Slit

Construction: Double slit nylon (PA6) corrugated conduit.

Colour: Black.

Typical Applications: Retrofit and cable assemblies with pre terminated plugs.

- Made from 2 interlocking slit corrugated conduits
- Temperature range -40°C to +120°C
- Cables can be inserted laterally
- Provides abrasion resistance and routing of cables for static applications
- Self extinguishing
- Halogen, sulphur and phosphorus free
- UV resistant
- Other colours available* in 21mm and 28mm Grey, Blue, Orange and White
- Also available in polypropylene in Black

part number	reel length (m)	outside dia (mm)	inside dia (mm)	min inside bend radius (mm)	pitch	nominal size (mm)	European (NW) sizes
TFPADS11*	50	11.5	6.2	70	F	10	7
TFPADS13	50	13.0	7.9	75	F	11	8
TFPADS16	50	15.8	10.3	10	F	13	10
					F	16	12
					F	18	14
					C	20	
					F	21	17
					C	21	
					C	25	
					F	28	23
TFPADS28	50	28.5	20.5	170	C	28	23
TFPADS34	25	34.5	26.6	180	C	34	29
					F	34	29
TFPADS42	25	42.5	32.0	200	C	42	36
TFPADS54	25	54.5	43.0	240	C	54	48
					C	67	56



Standards



BS EN IEC 61386

