

Trans Technical Solutions

Tel: +27 11 974 9679
Fax: +27 11 974 9653
Email: sales@ttsafrica.com

P O Box 5094
Delmenville
1403

Unit F11, Roete 24
Meadowdale
Germiston



SPB - Overbraided Enhanced EMI Screening Flexible Conduit



Type SPB
Overbraided,
Enhanced EMI Screening,
Flexible Conduit

Type SPB

Overbraided, Enhanced EMI Screening, Flexible Conduit

Materials: Galvanised Steel Conduit with PVC Covering, Galvanised Steel Overbraid

Part No.	Nominal Conduit Size	Outside Diameter	Inside Diameter	Min. Bend Radius	Reel Length
TSPB10	10mm	11.5mm	6.8mm	25mm	25m
TSPB12	12mm	15.5mm	10.3mm	25mm	25m
TSPB16	16mm	18.5mm	13.0mm	30mm	25m
TSPB20	20mm	23.0mm	16.9mm	35mm	25m
TSPB25	25mm	27.5mm	21.4mm	55mm	25m
TSPB32	32mm	35.5mm	28.1mm	60mm	10m
TSPB40	40mm	45.1mm	37.7mm	80mm	10m
TSPB50	50mm	57.5mm	48.4mm	90mm	10m

To order quote part number & reel length, e.g. TSPB12/25M

Approvals



IP Rating	Appropriate Fitting	Temperature Range	UV Resistance
For use with: Type SPB		Static Applications: -15°C to +70°C	Very High
IP54	Type SB - Type A & B	Moving Applications: -5°C to +90°C	
IP65	N/A	Flexibility & Fatigue Life	
IP66	N/A	High Flexibility - Medium Fatigue Life	
IP67	N/A	Fire Performance & EMI Screen	
IP68	N/A	Self Extinguishing	
IP69	N/A		