

Trans Technical Solutions

Tel: +27 11 974 9679
Fax: +27 11 974 9653
Email: sales@ttsafrica.com

P O Box 5094
Delmontville
1403

Unit F11, Roete 24
Meadowdale
Germiston



Plastic-Coated Stainless Steel Ball Ties - 304 and 316 SS

The nylon coating on these coated stainless steel cable ties, provides extra cable protection and corrosion resistance in extreme environments. These ball lock steel ties are self-locking, fast and easy to install.

Typical usages include mass transit, ship building, oil rigs, hazardous areas, mining, petrochemicals and rail industries.

Material: Stainless Steel 304 and 316 Grade
Temperature Range: -80°C to +150°C
Thickness: 0.25mm
Coating: Nylon
Flammability: Absolute fireproof



Part Number	Length x Width [mm]	Bundle Diameter [mm]	Steel Grade	Tensile Strength [N]
T/TDBT6SC	150x4.6mm	3-35mm	304 SS	35-45
T/TDBT8SC	200x4.6mm	3-40mm	304 SS	35-45
T/TDBT14SC	350x4.6mm	3-90mm	304 SS	35-45
T/TDBT8HC	200x8mm	3-40mm	304 SS	50-70
T/TDBT14HC	400 x8mm	4-105mm	304 SS	50-70
T/TDBT18HC	520 x8mm	4-150mm	304 SS	50-70
T/TDBT6SC316	150x4.6mm	3-35mm	316 SS	35-45
T/TDBT8SC316	200x4.6mm	3-40mm	316 SS	35-45
T/TDBT14SC316	350x4.6mm	3-90mm	316 SS	35-45
T/TDBT8HC316	200x8mm	3-40mm	316 SS	50-70
T/TDBT14HC316	400 8mm	4-105mm	316 SS	50-70