

Polyamide 6.6 cable ties - White

Premium cable ties with steel locking barb




- Several lengths and 6 typical widths with a tensile strength up to 780 N, to cover the most demanding applications
- Standard packaging is 1.000 / 500 pieces but smaller packaging (100 pieces) can also be supplied on request



E49405

Technical Information

Material - Moulding	Polyamide 6.6
Material - Locking barb	316 grade stainless steel
Temperature range	-40°C to +85°C
Flammability rating	UL 94 V-2
Other properties	Halogen free, Silicone free



Product Ref.	MIL Spec.	Length L [mm]	Width W [mm]	Thickness [mm]	Bundle diameter from ... to [mm]	Minimum tensile strength [N]	Quantity*** [pieces]	Tooling
T/TY23M-9	MS-3367-4	92	2.4	1.0	2 - 16	80	1000	T/ERG50 T/WT193A
T/TY232M-9	–	203	2.4	1.0	2 - 50	80	1000	
T/TY234M-9	–	356	2.4	1.0	2 - 102	80	1000	
T/TY24M-9	MS-3367-5	140	3.6	1.1	2 - 29	180	1000	
T/TY242M-9	–	204	3.6	1.1	2 - 50	180	1000	
T/TY26M-9	–	284	3.6	1.1	2 - 76	130	1000	
T/TY244M-9	–	368	3.6	1.1	2 - 103	130	1000	T/ERG50 T/ERG120 T/WT193A
T/TY25M-9	MS-3367-1	186	4.8	1.3	3.5 - 45	220	1000	
T/TY253M-9	MS-3367-7	295	4.8	1.3	3.5 - 78	220	1000	
T/TY28M-9	MS-3367-2	361	4.8	1.4	3.5 - 102	220	1000	
T/TY271M-9	–	150	7.6	1.5	6 - 31	540	500	
T/TY272M-9	–	223	6.9	1.6	6 - 50	540	500	
T/TY27M-9	MS-3367-3	340	6.9	1.6	6 - 90	540	500	T/ERG120 T/L-500-EU
T/TY275M-9	–	457	6.9	1.6	6 - 127	540	500	
T/TY277M-9	–	617	6.9	1.6	6 - 177	540	500	
T/TY29M-9	MS-3367-6	771	6.9	1.5	6 - 229	540	500	T/WT3D T/L-500-EU
T/TY53510M-9	–	889	8.2	1.7	to 254	780	50	
T/TY54513M-9	–	1143	8.2	1.7	to 330	780	50	

*** For smaller quantities, the figure "5" needs to be added to the part number immediately after "T/TY" - example: T/TY523M-2 is the same as T/TY23M-2 but in bags of 100