



Polyamide 6.6 cable ties - UV-resistant black


Premium cable ties with steel locking barb



E49405



BUREAU
VERITAS



- UV-resistant version, especially recommended for outdoor applications
- Black version (2% carbon for military specifications)
- Also available in heat stabilised + UV-resistant version, for outdoor applications that also require a resistance to high temperature (+105 °C).
- Several lengths and 6 typical widths with a tensile strength up to 780N, to cover the most demanding applications
- Packaging: OEM bulk quantities in recyclable polythene bags
- Also available in small bags with Euroslot and in workbench boxes

Technical Information

Material - Moulding	Polyamide 6.6
Material - Locking barb	316 grade stainless steel
Temperature range	-40°C to +85°C
Colour	Black
Flammability rating	UL 94 V-2
Other properties	UV-resistant, Halogen free, Silicone free

Product Ref.	MIL Spec.	Length L [mm]	Width W [mm]	Thickness [mm]	Bundle diameter from ... to [mm]	Minimum tensile strength [N]	Quantity [pieces]	Tooling
T/TY23MX	MS-3367-4	92	2.4	1.0	2 - 16	80	1000	T/ERG50 T/WT193A
T/TYB2315MX	–	178	2.4	1.0	2 - 38	80	1000	
T/TY232MX	–	203	2.4	1.0	2 - 50	80	1000	
T/TY234MX	–	356	2.4	1.0	2 - 102	80	1000	
T/TY24MX	MS-3367-5	140	3.6	1.1	2 - 29	180	1000	
T/TY242MX	–	204	3.6	1.1	2 - 50	180	1000	
T/TY26MX	–	284	3.6	1.1	2 - 76	130	1000	
T/TY244MX	–	368	3.6	1.1	2 - 103	130	1000	T/ERG50 T/ERG120 T/WT193A
T/TY25MX	MS-3367-1	186	4.8	1.3	3.5 - 45	220	1000	
T/TY253MX	MS-3367-7	295	4.8	1.3	3.5 - 78	220	1000	
T/TY28MX	MS-3367-2	361	4.8	1.4	3.5 - 102	220	1000	
T/TY271MX	–	150	7.6	1.5	6 - 31	540	500	
T/TY272MX	–	223	6.9	1.6	6 - 50	540	500	
T/TY27MX	MS-3367-3	340	6.9	1.6	6 - 90	540	500	
T/TY275MX	–	457	6.9	1.6	6 - 127	540	500	T/ERG120 T/L-500-EU
T/TY277MX	–	617	6.9	1.6	6 - 177	540	500	
T/TY29MX	MS-3367-6	771	6.9	1.5	6 - 229	540	500	
T/TY53510MX	–	889	8.2	1.7	to 254	780	50	T/WT3D
T/TY54513MX	–	1143	8.2	1.7	to 330	780	50	T/L-500-EU