

Self-locking Stainless Steel Cable Ties

Self-locking cable ties speed up installation with a unique self-locking head design that locks into any part of the tie. The smooth edges of 304 and 316 stainless steel promote worker safety in indoor, outdoor and underground environments.

Material: Stainless Steel
Operating temperature range: -60°C to +538°C
Colour: Natural



Part Number	Stainless Steel Type	Maximum Bundle Diameter	Length [mm]	Width [mm]	Thickness [mm]	Minimum Loop Tensile Strength (N)
T/MLT1S-CP	304 SS	2.5mm	127mm	4.6mm	0.2mm	890
T/MLT1S-CP316	316 SS	2.5mm	127mm	4.6mm	0.2mm	890
T/MLT2S-CP	304 SS	5.0mm	201mm	4.6mm	0.2mm	890
T/MLT2S-CP316	316 SS	5.0mm	201mm	4.6mm	0.2mm	890
T/MLT2.7S-CP	304 SS	5.9mm	259mm	4.6mm	0.2mm	890
T/MLT4S-CP	305 SS	10.0mm	362mm	4.6mm	0.2mm	890
T/MLT2H-LP	304 SS	10.0mm	201mm	7.9mm	0.2mm	2000
T/MLT2.7H-LP	304 SS	5.9mm	259mm	7.9mm	0.2mm	2000
T/MLT4H-LP	304 SS	10.0mm	362mm	7.9mm	0.2mm	2000
T/MLT4H-LP316	316 SS	10.0mm	362mm	7.9mm	0.2mm	2000
T/MLT6S-CP	304 SS	15.0mm	521mm	4.6mm	0.2mm	890
T/MLT8H-LP	304 SS	20.0mm	679mm	7.9mm	0.2mm	2000
T/MLT8S-CP	304 SS	20.0mm	679mm	4.6mm	0.2mm	2000