

Ball-Lock Type - Standard widths, fully coated

Stainless steel cable ties


The Ball-Lock Type stainless steel ties are self-locking, requiring no time consuming crimping or folding operations.

- Strong self-locking mechanism (stainless steel ball), with low insertion force
- Fast, easy and reliable installation
- Standard widths (4.6 mm & 7.9 mm), suitable for most applications, indoor and outdoor
- Corrosion resistant 316 grade stainless steel (marine grade) for high mechanical and chemical durability
- Fully coated version with non-toxic, halogen free Polyester coating, for a superior protection of cables and installer's hands and for an improved insulation between dissimilar materials.
- Applications: installation of cables and pipes in extreme conditions and hazardous areas, such as: petrochemical and food processing industries, power stations, mining, shipbuilding, offshore and other aggressive environments



Technical Information

Material	316 grade non-magnetic stainless steel
Coating	Polyester
Temperature range	-80°C to +150°C
Colour	Black
Flammability rating	Absolutely fireproof
Other properties	UV-resistant, Halogen free, non toxic



Product Ref.	Length L [mm]	Width W [mm]	Material thickness [mm]	Maximum bundle diameter [mm]	Minimum tensile strength [N]	Quantity [pieces]	Tooling
TYLS-4.6-100BC	100	4.6	0.36	20	440	100	CT3 CT6
TYLS-4.6-125BC	125	4.6	0.36	22	440	100	
TYLS-4.6-150BC	150	4.6	0.36	24	440	100	
TYLS-4.6-200BC	200	4.6	0.36	50	440	100	
TYLS-4.6-300BC	300	4.6	0.36	80	440	100	
TYLS-4.6-360BC	360	4.6	0.36	100	440	100	
TYLS-4.6-520BC	520	4.6	0.36	150	440	100	
TYLS-4.6-680BC	680	4.6	0.36	200	440	100	
TYLS-4.6-840BC	840	4.6	0.36	250	440	100	
TYLS-4.6-1000BC	1000	4.6	0.36	300	440	100	
TYLS-4.6-1200BC	1200	4.6	0.36	365	440	100	
TYLS-4.6-1400BC	1400	4.6	0.36	425	440	100	
TYLS-7.9-100BC	100	7.9	0.36	20	530	100	
TYLS-7.9-125BC	125	7.9	0.36	22	530	100	
TYLS-7.9-150BC	150	7.9	0.36	24	530	100	
TYLS-7.9-200BC	200	7.9	0.36	50	530	100	
TYLS-7.9-300BC	300	7.9	0.36	80	530	100	
TYLS-7.9-360BC	360	7.9	0.36	100	530	100	
TYLS-7.9-520BC	520	7.9	0.36	150	530	100	
TYLS-7.9-680BC	680	7.9	0.36	200	530	100	
TYLS-7.9-840BC	840	7.9	0.36	250	530	100	
TYLS-7.9-1000BC	1000	7.9	0.36	300	530	100	
TYLS-7.9-1200BC	1200	7.9	0.36	365	530	100	
TYLS-7.9-1400BC	1400	7.9	0.36	425	530	100	